

[http://web.promix.info/kat/LUUD-H%C3%B6gtalare.pdf](#)
(1) Facebook
caraudioforum.it
omnitrronic subwoofer | eBay
web.promix.info

technical specifications.						
Product:	BX-1250	BX-1550	BX-1850	BX-2250	BX-2550	BX-2850
Rated power:	300 W RMS	400 W RMS	600 W RMS	400 W RMS	600 W RMS	700 W RMS
Program power:	600 W	800 W	1200 W	800 W	1200 W	1400 W
Bass:	12"	15"	18"	2 x 12"	2 x 15"	2 x 18"
Connections:	2 Speaker-sockets	2 Speaker-sockets	2 Speaker-sockets	2 Speaker-sockets	2 Speaker-sockets	2 Speaker-sockets
Max. SPL (1 m):	96 dB	97 dB	99 dB	96 dB	101 dB	101 dB
Impedance:	8 Ohms	8 Ohms	8 Ohms	8 Ohms	8 Ohms	8 Ohms
Frequency range:	20 - 400 Hz	20 - 300 Hz	15 - 300 Hz	20 - 400 Hz	15 - 300 Hz	15 - 300 Hz
Dimensions (H x W x D):	480 x 390 x 320 mm	585 x 470 x 455 mm	675 x 545 x 455 mm	745 x 390 x 320 mm	900 x 465 x 455 mm	1220 x 530 x 420 mm
Weight:	12 kg	19.5 kg	27 kg	19 kg	34 kg	47 kg

+

+

Passive crossover

Compatible to BX / TX / TMX series

Professional workmanship

No. 11037705.....BX-1250

No. 11037711.....BX-1550

No. 11037731.....BX-1850

No. 11037745.....BX-2250

No. 11037751.....BX-2550

No. 11037772.....BX-2850

• High-pressure bass support for all top speakers • Powerful, dry bass via voluminous housing and bass-reflex tubes • Very high durability • Passive crossover, switchable • With bar handles • Scratch-resistant, black felt-covering • Strong protective grille for perfect protection • With stable protective steel corners • With flange for top speaker installation • Compact speaker-system for car transport • Ideal for mobile discotheques or for permanent installation in discotheques etc.

Accessories:

Distance tube bassbox/satellite 80cm	No. 60004550
Distance tube bassbox/satellite 100cm	No. 60004552
Distance tube bassbox/satellite 120cm	No. 60004554
Speaker-cable 3m PROFI 2x2.5mm ²	No. 3022105N
Clamping belt S200 with lock 5m/25mm yell	No. 60206780
Clamping belt S400 w.ratchet 5m/25mm blue	No. 60206785
EUROLITE TV-35 TV-pin for speakers	No. 60000735

19.19

11/07/2013